

HCS-40



**ALSO AVAILABLE
IN PEDESTAL MOUNT!**

A REAL PRODUCT, FOR THE REAL WORLD. The HCS from ClipperCreek is designed to take the wear-and-tear of everyday use in all environments. Its tough NEMA 4 outdoor rated enclosure ensures you can install this unit anywhere with confidence.

- **FAST CHARGING** – 7.7 kW of power to charge your vehicle fast!
- **QUALITY** – Technology that works for the life of your current plug-in vehicle and then some
- **CONVENIENT** – 25 feet of charging cable for installation and operation flexibility
- **DURABLE** – Rugged, fully sealed NEMA 4 enclosure for installation anywhere
- **RELIABLE** – Backed by ClipperCreek's 3-year warranty, and outstanding customer service



ClipperCreek.com

HCS-40

PRODUCT OVERVIEW

QUESTIONS? TO ORDER!

Call ClipperCreek Today!

530-887-1674

www.clippercreek.com



Optional Holster
for wall mount

ELECTRICAL SPECIFICATIONS

- **Service:** 208V to 240V - 40A, dedicated circuit
- **Charge current output power:** 208V to 240V - 32A max
- **Service ground monitor:** Constantly checks for presence of proper safety ground
- **Automatic circuit reclosure after minor power faults**
- **Charge circuit interruption device:** Ground fault protection with fully automated self-test - eliminates manual user testing

MATERIAL SPECIFICATIONS

- Indoor/outdoor rated (NEMA 4) enclosure
- Operating Temperatures: -22°F to 122°F (-30°C to 50°C)
- 9" W x 19.7" H x 5.3" D (229mm W x 493mm H x 135mm D)
- Installation: Hardwire or plug connected
- 25 feet charging cable - standard
- Optional Holster
- ETL Listed

AVAILABLE AS



PLUG-IN

CODES, STANDARDS and RECOMMENDED PRACTICES

- **UL 2594** Electric Vehicle Supply Equipment
- **UL 2231** Personal Protection Device
(i.e., CCID Hardware)
- **UL 1998** Standard for Safety-Related Software
- **NEC 625** Electric Vehicle Charge System
- **SAE-J1772™** Electric Vehicle Conductive Charge Coupler

model: HCS-40P

plugs available

NEMA 14-50
NEMA 6-50

